

Description (Sample Specification Language)

Pipe support materials shall be selected to provide an adequate anchoring point that addresses the lightweight flexible nature of Gastite/FlashShield Flexible Gas Piping. This can be accomplished through either the weight of the support or by anchoring the support to the roof materials. The support materials must also be selected to be non-damaging to the roofing material. (Check with the roof material manufacturer for approved adhering methods and non-damaging materials/installations)

Features:

- Quick & Easy Installation
- Will Not Damage Roof
- Effectively Anchors Gastite CSST
- Effectively Supports other Fuel Gas Piping
- 100% Recycled Material
- UV Resistant & Waterproof
- Installs With or Without Standard Roof Adhesives
- Handles Multiple Pipe Runs



Technical Data:

General

Support Material	Rubber
Hardware Material	Galvanized Carbon Steel



Dimensional Characteristics

Part Number	Description	Dimensions	Weight (Lbs)
RB0-10-4	Rubber Support Block	10"L X 4"ht	4.3
RB1-10-5	Rubber Support Block with 7/8" Galv. Steel channel	10"L X 5"ht	5.5
RB1-29-5	Rubber Support Block with 7/8" Galv. Steel channel	29"L X 5"ht	16.3
RB2-10-12	Rubber Support Block with adjustable height 7/8" Galv. Steel channel	10"L X 5" to 12"ht	6.6