

Description (Sample Specification Language)

Gastite/FlashShield requires a minimum of six inches of conduit at termination points not covered by the ANSI standard and can be used to provide additional protection from puncture threats.

Features:

- Quick and easy installation

Technical Data:

General

Conduit Material	Galvanized Steel
Conduit Construction	Strip-Wound Interlocking
(L)Floppy-xx	1ft Cut Lengths
Floppy-xx	Coil Length: see Table



Dimensional Characteristics

P/N	For CSST Size	Nom Conduit Size	Wall Thickness	Coil Length	Coil Weight (lbs)	Cut Length (1ft) Weight (lbs)
(L)Floppy-12	3/8"	3/4"	0.010"	50'	8.4	0.19
(L)Floppy-16	1/2"	1"	0.010"	50'	13.1	0.38
(L)Floppy-20	3/4"	1-1/4"	0.012"	25'	11.0	0.47
(L)Floppy-24	1"	1-1/2"	0.012"	25'	13.1	0.58
(L)Floppy-28	1-1/4"	1-3/4"	0.012"	25'	16.5	0.68
(L)Floppy-36	1-1/2"	2-1/4"	0.015"	25'	28.2	1.15
(L)Floppy-48	2"	3"	0.015"	25'	36.0	1.48