

## Gastite XR2 Fitting, XR2FTG-NF

### Description (Sample Specification Language)

Gastite® is a corrugated stainless steel tubing complying with ANSI LC 1 "Fuel Gas Piping Systems Using CSST" and listed with CSA®, ICC and IAPMO. Manufacturing materials are: ASTM A240 type 300 corrugated stainless steel tubing with a minimum wall thickness of .010", jacketing of UV resistant polyethylene meeting the requirements of ASTM E84 for flame spread and smoke density. All mechanical tube fittings are SAE CA360 brass incorporating double wall flare sealing and Jacket-Lock™ jacket capturing for steel tubing protection.

### Features:

- Quick & Easy Installation
- Required Tools: Tubing Cutter, Utility Knife, Wrenches
- Fewer Fittings, Less Waste
- Technical Support
- Approved for Concealed Use
- Tool-Less Flare Fitting Design
- Metal-to-Metal Seal
- Self-Guiding Fitting Assembly
- Patented Jacket-Lock™
- Fully Reusable Fitting
- Patent Pending Multi-Point Seal




### Applicable Standards & Listings:

- CSA: ANSI LC 1 "Fuel Gas Piping Systems Using Corrugated Stainless Steel Tubing" – Certificate No. 1009875
- ICC: International Code Council – Evaluation Report No. ESR-1031
- IAPMO: International Association of Plumbing & Mechanical Officials - File No. C-3250

### Technical Data:

#### General

Max. Approved Operating Pressure	5 psi
Recommended Test Pressure	50 psi
Operating Temperature Range	-100°F to 400°F
Fitting Material	CA360



### Dimensional Characteristics

Size	P/N	Assembled Length	Pipe Thread (NPT)	Flange Thread (NPT)	Nut Hex	Fitting Hex	Assembly Torque (ft-lbs)	Weight (lbs)
3/8"	XR2TRM-6-NF	2.062"	1/2"	1/2"	1	7/8	25	0.24
1/2"	XR2TRM-8-NF	2.124"	1/2"	3/4"	1-1/4	1-1/8	35	0.33
3/4"	XR2TRM-11-NF	2.351"	3/4"	1"	1-1/2	1-5/16	45	0.49
1"	XR2TRM-16-NF	2.427"	1"	1-1/4"	1-7/8	1-11/16	65	0.74
1-1/4"	XR2TRM-20-NF	2.728"	1-1/4"	1-1/2"	2-1/8	2	95	1.01
1-1/2"	XR2TRM-24-NF	2.92"	1-1/2"	2"	2-1/2	2-5/16	120	1.63
2"	XR2TRM-32-NF	3.442"	2"	2-1/2"	3-1/8	2-15/16	150	2.63