

Gastite Steel Conduit, (L)FLOPPY

Description (Sample Specification Language)

Gastite® is a corrugated stainless steel tubing complying with ANSI LC 1b "Fuel Gas Piping Systems Using CSST" and listed with CSA®, ICBO and IAPMO. Manufacturing materials are: ASTM A240 type 300 corrugated stainless steel tubing with a minimum wall thickness of .010", jacketing of UV resistant polyethylene meeting the requirements of ASTM E84 for flame spread and smoke density. All mechanical tube fittings are SAE CA360 brass incorporating double wall flare sealing and Jacket Lock™ jacket capturing for steel tubing protection.

Features:

- Quick & Easy Installation
- Required Tools: Tubing Cutter, Utility Knife, Wrenches
- Fewer Fittings, Less Waste
- Technical Support
- Approved for Concealed Use
- Tool-Less Flare Fitting Design
- Metal-to-Metal Seal
- Self-Guiding Fitting Assembly
- Patented Jacket-Lock™
- Fully Reusable Fitting
- Provides additional protection from puncture threats



Technical Data:

General

Conduit Material	Galvanized Steel
Conduit Construction	Strip-Wound Interlocking
Floppy-xx	1ft Cut Lengths
Lfloppy-xx	Coil Length: see Table

Dimensional Characteristics

P/N	For CSST Size	Nom Conduit Size	Wall Thickness	Coil Length	Coil Weight (lbs)	Cut Length Weight (lbs)
(L)Floppy-12	3/8"	3/4"	0.010"	50'	8.4	0.19
(L)Floppy-16	1/2"	1"	0.010"	50'	13.1	0.38
(L)Floppy-20	3/4"	1-1/4"	0.012"	25'	11.0	0.47
(L)Floppy-24	1"	1-1/2"	0.012"	25'	13.1	0.58
(L)Floppy-28	1-1/4"	1-3/4"	0.012"	25'	16.5	0.68
(L)Floppy-36	1-1/2"	2-1/4"	0.015"	25'	28.2	1.15
(L)Floppy-48	2"	3"	0.015"	25'	36.0	1.48