



## FlashShield Termination Bracket Fitting, FSTRMBKT-XX




**Gastite Division**  
 1116 Vaughn Parkway  
 Portland, TN 37148  
 Telephone 800-662-0208  
 www.Gastite.com

### Description

FlashShield™ is metallically shielded corrugated stainless steel tubing system complying with ANSI LC 1 "Fuel Gas Piping Systems Using CSST" and listed with CSA®, ICC and IAPMO. The FlashShield system is also listed to protective jacket standards, ICC-ES PMG LC1024, and LC1027. All mechanical tube fittings are SAE CA360 brass incorporating double wall flare sealing and Jacket-Bite™ jacket capturing for steel tubing protection and continuous conductivity.

### Features:

- Termination Fitting (male adapter, bushing, termination nut) Bracket and Jam Nut
- Approved for Concealed Use
- Tool-Less Flare Fitting Design
- Metal-to-Metal Seal
- Self-Guiding Fitting Assembly
- Patented Jacket-Bite™
- Fully Reusable Fitting
- Patent Pending Multi-Point Seal




### Listings:

- CSA Certificate 2728525
- ICC-ES Report No. PMG 1066 and PMG 1155
- IAPMO: File No. C-3250 and Report No. 0239

### Technical Data:

Max. Approved Operating Pressure	25 psi
Operating Temperature Range	-35°F to 160°F
Fitting Material	CA360



### Dimensional Characteristics

Size	P/N	Pipe Tread	Flange Thread	Nut Hex	Fitting Hex	Bracket Height	Bracket Width	Bracket Length	Assembly Torque (ft-lbs)
1/2"	FSTRMBKT-8	1/2"	3/4"	1-1/4"	1-1/8"	2-1/2"	2"	2-1/2"	35
3/4"	FSTRMBKT-11	3/4"	1"	1-9/16"	1-3/8"	2-1/2"	2"	2-1/2"	45
1"	FSTRMBKT-16	1"	1-1/4"	1-15/16"	1-3/4"	3"	3"	3-3/4"	65
1-1/4"	FSTRMBKT-20	1-1/4"	1-1/2"	2-3/16"	2-1/16"	3"	3"	3-3/4"	95

FlashShield fittings can be used with Gastite and FlashShield CSST.