

Gas Load Center, GLC1

Gastite Division 1116 Vaughn Drive Portland, TN. 37148 Telephone 800-662-0208 www.gastite.com

Description (Sample Specification Language)

The Gastite® Gas Load Center creates a recessed cabinet for more polished looking manifold assemblies. The Gas Load Center is capable of organizing and securing multiple Gastite runs, manifold, union, small regulator, drip leg, and shut-off valves. For assemblies requiring a union, valve, bonding clamp, or regulator, this provides a recessed mounting option while allowing code required accessibility. (Check local codes to determine what is required for an approved manifold or regulator assembly).

Features:

- Quick & Easy Installation
- Fits within 16" on center wall cavities.
- Used on steel and timber framing
- Provides a secure manifold assembly.
- · Vertical channels for variable bracket positioning.
- Includes labeling sticker for gas run information.
- Six knockouts top and bottom.
- Kit Contains: mounting box, trim flange, manifold bracket and mounting hardware.
- Optional louvered panel shown below.
- For use with manifolds 3-PORTMAN, 3-PORTMAN-1 and 4-PORTMAN





Technical Data:

General:

	Box Material		20 Gaug	ge Steel		
Ī	Box Color/Coa	ating	White/Polyester Powder coat			
Ī	Manifold Brac	ket	MBRACE-2 (Secures 1.06"-1.30" OD Pipe)			<u>e)</u>
Ī	Bracket Mater	rial	16 Gauge Galvanized Steel			
Ī	Hardware Incl	luded	2 x 5/16" U-bolt – Coarse Thread			
			4 x 5/16	" Wing Nເ	ıts – Coarse Thread	
				Denth	DEPTH HEIGHT	
	P/N	Width	Height	Depth	Knock-Out	
	GLC1	14-1/2"	22"	4"	1.13" Diameter	/ \