

**Description:**

XR3 (rev. 2) series mechanical brass fittings are specifically designed for use with Gastite®, FlashShield®, and FlashShield+™ flexible gas piping systems complying with ANSI LC 1 "Fuel Gas Piping Systems Using CSST". The self-flaring fitting produces a metal-to-metal seal, and is reusable. Jacket-Lock®, Metal Lock, Arc-Trap™, and multi-point seal features are incorporated into the fitting.

**Components:**

- Tee Body, (3) Split Bushings, (3) Nuts

**Features:**

- Tool-Less Flare Fitting Design
- Metal-to-Metal Seal
- Multi-Point Seal
- Jacket-Lock®
- Arc-Trap™ (FlashShield+ only)
- Metal Lock (FlashShield only)
- Fully Reusable Fitting
- Approved for Outdoor and Concealed Use

DROP

RUN B



RUN A

**Listings:**

- CSA Certificate 2728525
- ICC-ES Report No. PMG 1155
- IAPMO: Report No.3250 and Report No. 0239

**Technical Data:**

Maximum Operating Pressure	25 psi
Operating Temperature Range	-40°F to 160°F
Fitting Material	CA360 Brass

**Dimensional Characteristics**

P/N	Run A		Run B		Drop	
	CSST	HEX	CSST	HEX	CSST	HEX
XR3T-8	1/2"	1-1/4 "	1/2"	1-1/4 "	1/2"	1-1/4 "
XR3T-11	3/4"	1-9/16 "	3/4"	1-9/16 "	3/4"	1-9/16 "
XR3T-16	1"	1-15/16 "	1"	1-15/16 "	1"	1-15/16 "
XR3T-11-8-8	3/4"	1-9/16 "	1/2"	1-1/4 "	1/2"	1-1/4 "
XR3T-11-11-8	3/4"	1-9/16 "	3/4"	1-9/16 "	1/2"	1-1/4 "
XR3T-16-11-8	1"	1-15/16 "	3/4"	1-9/16 "	1/2"	1-1/4 "
XR3T-16-11-11	1"	1-15/16 "	3/4"	1-9/16 "	3/4"	1-9/16 "
XR3T-16-16-8	1"	1-15/16 "	1"	1-15/16 "	1/2"	1-1/4 "
XR3T-16-16-11	1"	1-15/16 "	1"	1-15/16 "	3/4"	1-9/16 "